



# Safety Data Sheet

SDS No. SST-6422-110916

Conforms to HazCom 2012/U.S.



## Section 1: IDENTIFICATION

**Product Name(s):** CML Liquid Blend

**Product Identifiers:** Cold Mix Binder, Cold Mix Asphalt Cement Binder, Cold Patch Binder, Cold Patch Asphalt Cement Binder.

**Manufacturer and/or Marketer:** S&S Terminal, Inc.  
1731 Old State Route #7  
P.O. Box 66  
Rayland, Ohio 43943

**Information Telephone Number:**  
1-740-859-2131 (8am to 5pm EST)

**For Chemical Emergency ONLY:**  
(spill, leak, fire, exposure or accident)

**CHEMTREC**  
**1-800-424-9300 24 HOURS / 7 Days**

**Product Use:** CML Liquid Blend is the cement used for cold mix asphalt in repairing paving roads, driveways, parking lots, school yards, and other surface, base, or sub-base applications.

**Note:** This MSDS covers different blends of CML Liquid Blend. Individual composition of hazardous constituents will vary between CML Liquid Blend mix designs.

## Section 2: HAZARD(S) IDENTIFICATION

**Hazard Classifications:** Category 2, Health Hazard. Skin Irritation  
Category 1, Health Hazard. Skin Sensitization  
Category 2, Health Hazard. Eye Irritation  
Category 2, Health Hazard. Carcinogenicity / Inhalation  
Category 4, Fire Hazard. Combustible Liquid



NFPA



WARNING



WARNING

**Hazard Statements:** Combustible Liquid – Keep from Flame or Sources of Ignition  
May produce Hydrogen Sulfide Gas at Elevated Temperatures  
May cause skin Irritation  
May cause allergic skin reactions.  
May cause eye Irritation.  
Possibly carcinogenic to humans.

## Precautionary Statements:

- Eye Contact:** Eye contact with CML Liquid Blend may cause moderate eye irritation, redness, and itching. Eye exposures require immediate first aid to prevent damage to the eye.
- Skin Contact:** Repeated or prolonged contact to CML Liquid Blend may cause dry skin, discomfort, irritation, and dermatitis. If heated, direct contact with CML Liquid Blend will cause severe thermal burns
- Inhalation (acute):** If heated, CML Liquid Blend may release irritating fumes or vapors such as smoke, carbon dioxide, carbon monoxide, unburned hydrocarbons. Hydrogen sulfide and other sulfur-containing gases can evolve from this product at elevated temperatures. Exposure to fumes or vapors may cause irritation of the nose and throat, and symptoms such as headache, dizziness, loss of coordination, and drowsiness.
- Carcinogenicity:** Cold Mix Asphalt Cement is not listed as a carcinogen by ACGIH. Presently, the IARC has determined that there is inadequate evidence that bitumens alone are carcinogenic to humans.
- Ingestion:** Ingestion may result in nausea, vomiting, diarrhea, and restlessness.
- Medical Conditions Aggravated by Exposure:** Individuals with preexisting skin conditions can be aggravated by exposure.

## Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Component	Percent (% wt)	CAS Number	ACGIH Exposure	OSHA PEL
Liquid Asphalt Cement	60-85	8052-42-4	0.5 mg/m <sup>3</sup>	NA
Petroleum Hydrocarbon Mixture	10-30	68334-30-5	100 mg/m <sup>3</sup>	NA
Anti-stripping agent	0-4	1338-23-4	NA	NA

- Note:** CML Liquid Blend may also contain small amounts of asphalt modifiers (e.g. anti-stripping agents, hydrated lime).

## Section 4: FIRST AID MEASURES

- Eye Contact:** For contact with CML Liquid Blend, rinse eyes thoroughly with water for at least 15 minutes, including under the lids, to remove all particles. Check for and remove any contact lenses. Seek medical attention.
- Skin Contact:** Wash with cool water and a pH neutral soap or a mild skin detergent. Do not use solvents or thinners to remove material from skin. Seek medical attention for burns, rash, irritation, and dermatitis. For contact with hot material, immerse or flush skin with cold water for at least 15 minutes. Call a physician. Do not attempt to remove solidified material, since removal may cause further tissue injury. Remove contaminated clothing and shoes. Thoroughly clean clothing and shoes before reuse.
- Inhalation:** Move person to fresh air. If breathing is difficult, administer oxygen. If not breathing or if no heartbeat, give artificial respiration or cardiopulmonary resuscitation (CPR). Immediately call a physician. Seek medical attention for discomfort or if coughing or other symptoms do not subside.
- Ingestion:** Do not induce vomiting. Seek medical attention and/or contact poison control center immediately.

## Section 5: FIREFIGHTING MEASURES

---

<b>Specific Hazards:</b>	This product is not a combustible liquid per the OSHA Hazard Communication Standard, but will ignite and burn with contact with direct flame or ignition source.
<b>Extinguishing Agent:</b>	For small fires, Class B fire extinguishing media such as CO <sub>2</sub> , dry chemical, foam (AFFT/ATC) can be used. For larger fires, water spray, fog or foam (AFFT/ATC) can be used. Fire fighting should be attempted only by those who are adequately trained and equipped with proper protective equipment
<b>Firefighting Equipment:</b>	A SCBA is recommended to limit exposure to combustion products when fighting any fire.
<b>Combustion Products:</b>	Toxic gases produced in a fire include but not limited to CO, CO <sub>2</sub> , and H <sub>2</sub> S.
<b>NFPA Rating:</b>	Health: 1      Flammability: 2      Reactivity: 1      Other: ---

## Section 6: ACCIDENTAL RELEASE MEASURES

---

<b>General:</b>	Dike or contain spill with soil, floor-dry, sand, etc. Pump liquid to containers or storage vessel. Soak up residue with absorbent material. Use a shovel to scrape up material and place material into suitable containers for recovery or disposal. Do not wash CML Liquid Blend down sewage and drainage systems or into bodies of water (e.g. streams). Wear appropriate protective equipment as described in Section 8.
<b>Waste Disposal Method:</b>	Recovered materials may be blended with aggregate and used for patching or other maintenance use. Dispose of CML Liquid Blend according to Federal, State, Provincial, and Local regulations.

## Section 7: HANDLING AND STORAGE

---

<b>General:</b>	Handle with care and use appropriate control measures. Avoid contact with skin, eyes, and clothing. Microbial degradation and other change may occur on very extended storage. Maintain employee exposure levels below established regulatory limits. Use all appropriate Personal Protective Equipment (PPE) described in Section 8.
<b>Usage:</b>	Personal Protective Equipment (PPE) described in Section 8.  Concentrations of hydrogen sulfide (H <sub>2</sub> S) can be generated and accumulated in storage tanks and bulk transport compartments which may require additional precautions and procedures during loading and unloading.
<b>Storage:</b>	Store in appropriately labeled, clean covered tanks between 10°C and 30°C. Avoid freezing. Do not expose to open flames, strong oxidizers or other source of ignition.
<b>Clothing:</b>	Remove and launder clothing that is soiled with CML Liquid Blend. Thoroughly wash hands and exposed skin after exposure to CML Liquid Blend.

## Section 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

---

Component	OSHA PEL	ACGIH-TLV-TWA	NIOSH REL
Asphalt	N/A	0.5 mg/m <sup>3</sup>	N/A
Petroleum Hydrocarbon Mixture	N/A	100 mg/m <sup>3</sup>	N/A
Anti-Stripping Additive	N/A	NA	N/A

**Engineering Controls:** Under normal conditions, engineering controls are not required. Use local exhaust or general dilution ventilation when using at elevated temperatures or during activities that generate dust or fumes, to maintain levels below exposure limits.

**Personal Protective Equipment (PPE):**

Respiratory Protection: Under ordinary conditions no respiratory protection is required. Wear a NIOSH approved respirator that is properly fitted and is in good condition when exposed to dust or fumes above exposure limits.

Eye Protection: Wear ANSI approved glasses, safety goggles, or face shield when handling CML Liquid Blend to prevent contact with eyes.

Skin Protection: Wear leather or cloth work gloves to prevent skin contact and insulated gloves when handling CML Liquid Blend material. Thoroughly wash hands and exposed skin after exposure to CML Liquid Blend.

---

**Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

**Physical State:** Liquid

**Appearance:** Black-Dark Brown Solid or Semi-Solid

**Odor:** Slight Petroleum / Tar Odor

**Vapor Pressure:** No Data Available

**Vapor Density:** No Data Available

**Specific Gravity:** 0.960 – 0.980

**Evaporation Rate:** No Data Available

**pH (In Water):** No Data Available

**Melting Point:** No Data Available

**Freezing Point:** No Data Available

**Boiling Point:** 293° F - 707° F

**Flash Point:** 234.7° F

**Auto-Ignition Temp.** No Data Available

**Flammability (solid, gas)** No Data Available

**Flammable Lower Limit:** 0.07 % in air

**Flammable Upper Limit:** 6.0% in air

**Viscosity:** No Data Available

**Solubility in Water:** Insoluble

**Relative Density:** No Data Available

**Decomposition Temperature:** No Data Available

**Partition Coefficient: N-Octanol/water:** No Data Available

## Section 10: STABILITY AND REACTIVITY

---

<b>Stability:</b>	Stable.
<b>Chemical Stability:</b>	Avoid contact with incompatible materials, excessive heat, sources of ignition and open flames. Incompatible with strong acids or bases, and oxidizing agents such as nitrates, chlorates, and peroxides.
<b>Other:</b>	<b>Hazardous Decomposition:</b> When heated, may produce hydrogen sulfide and various hydrocarbons.

## Sections 11: TOXICOLOGICAL INFORMATION

---

Primary Routes of Exposure:	Inhalation:	Dermal:	Oral:
	Yes	No	Yes

### Summary of health effect data on asphalt components:

WHO/International Agency for Research on Cancer in the basis of an earlier meta-analysis, the IARC multi-center study and several more recent independent studies, the Working Group concluded that there was inadequate evidence in humans for the carcinogenicity of occupational exposures during road paving with straight-run bitumens. Also, there was inadequate evidence in experimental animals for the carcinogenicity of extracts and of fume condensates of this type of bitumens. However, studies of workers exposed to bitumen emissions during paving with straight-run bitumens showed mutagenic and genotoxic/cytogenetic effects in these workers. Similar effects were also observed in experimental systems under controlled conditions. This strong mechanistic evidence led to the classification of occupational exposures to straight-run bitumens and their emissions during road paving as "possibly carcinogenic to humans" (Group 2B).

This product can produce a toxicologically significant concentration of hydrogen sulfide (H<sub>2</sub>S) when enclosed in a confined space. Hydrogen sulfide gas (H<sub>2</sub>S) is toxic by inhalation. Prolonged breathing of 50-100 ppm H<sub>2</sub>S vapors can produce eye and respiratory tract irritation. Higher concentrations (250-600 ppm) for 15-30 minutes can produce headache, dizziness, nervousness, nausea and pulmonary edema or bronchial pneumonia. Concentrations of >1000 ppm will cause immediate unconsciousness and death through respiratory paralysis. Rats and mice exposed to 80 ppm H<sub>2</sub>S, 6 hrs/day, 5 days/week for 10 weeks, did not produce any toxicity except for irritation of nasal passages. H<sub>2</sub>S did not affect reproduction and development (birth defects or neurotoxicity) in rats exposed to concentrations of 75-80 ppm or 150 ppm H<sub>2</sub>S, respectively. Over the years a number of acute cases of H<sub>2</sub>S poisonings have been reported. Complete and rapid recovery is the general rule.

However, if the exposure was sufficiently intense and sustained causing cerebral hypoxia (lack of oxygen to the brain), neurologic effects such as amnesia, intention tremors or brain damage are possible.

Some epidemiologic studies conducted on workers exposed to asphalt fume have shown no increased incidence of cancer while other studies have reported a slightly increased incidence of lung, other respiratory tract or gastrointestinal cancers. In those studies in which elevated cancer incidences were reported, concurrent or previous exposure to coal-tar products have been documented. therefore, it cannot be concluded that cancer incidence is related to exposure to asphalt fume.

Although early studies have some technical shortcomings, long term inhalation exposures to asphalt aerosols or fumes did not produce evidence of carcinogenicity even though chronic inflammatory changes similar to those produced by nonspecific respiratory irritants were observed. Inhalation of 150 mg/m<sup>3</sup> asphalt fume (particulate + vapor) 6 hours/day, 5 days/week for 13 weeks, did not produce toxicity except for reduced body weight and irritation in nasal passages in exposed rats.

Laboratory animals administered subcutaneous or intramuscular injections of asphalt preparations or repeated skin applications of hot (212 F) undiluted asphalt have occasionally produced a low incidence of skin tumors at the site of application. These findings are of questionable validity since repeated tissue trauma (and/or burns) at the application site can induce tumors. Solvent dilutions of different types of asphalts have been tested in chronic skin painting studies. Some of the studies have reported a low incidence of skin tumors. The use of diluents may enhance bioavailability or metabolic activation of chemicals in the mixture in a fashion not representative of occupational exposure. Skin painting studies in mice have been conducted using condensates from fumes generated at temperatures >450 F diluted in solvent. Asphalt fume condensate preparations have produced skin tumors. Experimental conditions (temperature and dose) were grossly exaggerated over that likely to occur in humans.

Extracts of whole asphalts tested in a modified Ames assay gave negative or slightly positive findings (mutagenicity index <1.5). Fume condensates derived from heating asphalts to high temperatures (>450 F) were moderately active (MI 4-9).

Fumes generated from coal tar pitch were >1000 times more active. Asphalt fume samples collected under actual field conditions did not show any significant mutagenic activity.

## Section 12: ECOLOGICAL INFORMATION

---

**Ecotoxicity Effects:** If spilled, CML Liquid Blend may release the oil components of the mixture and could harm plant and aquatic life in low concentrations. This product does not concentrate or accumulate in the food chain. If released to soil and water, this product is expected to biodegrade under both aerobic and anaerobic conditions.

## Section 13: DISPOSAL CONSIDERATIONS

---

Dispose of waste and containers according to Federal, State, Provincial, and Local regulations.

## Section 14: TRANSPORT INFORMATION

---

This product is regulated under 49 CFR, asphalt cutback liquid, combustible liquid (USA).

**U.N.Number:** 1999; Packing Group: III.

**Primary Classification:** 3; Subsidiary Classification: 9.2

## Section 15: REGULATORY INFORMATION

---

### Federal Regulatory Information:

**US TSCA Chemical Inventory Section 8(b):** This product and/or its components are listed on the TSCA Chemical Inventory.

### OSHA / MSHA Hazard Communication Standard:

This product has been evaluated and determined to be hazardous as defined in OSHA's Hazard Communication Standard.

### EPA Superfund Amendment & Reauthorization Act (SARA):

**SARA Section 302:** This product produces the following component(s) that have been Listed on the EPA's Extremely Hazardous Substance (EHS) List:  
- Hydrogen Sulfide (H<sub>2</sub>S) -

**SARA Section 304:** This product is not listed as a CERCLA hazardous substance.

**SARA Section 311/312:** The following EPA hazard categories apply to this product:  
- Acute - Health – Hazard -

**SARA Section 313:** This product contains none of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

**RCRA:** If discarded in its purchased form, this product would not be a hazardous waste either by listing or characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste.

## Section 16: OTHER INFORMATION

---

### Abbreviations:

ACGIH	American Conference of Governmental Industrial Hygienists	NTP	National Toxicology Program
(B)	Inhalable fraction, as benzene – soluble aerosol	OSHA	Occupational Safety and Health Administration
CAS No	Chemical Abstract Service number	PEL	Permissible Exposure Limit
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act	pH	Negative log of hydrogen ion
CFR	Code of Federal Regulations	PPE	Personal Protective Equipment
DOT	U. S. Department of Transportation	(RP)	Respirable Particulate
EST	Eastern Standard Time	RCRA	Resource Conservation and Recovery Act
IARC	International Agency for Research on Cancer	SARA	Superfund Amendments and Reauthorization Act
MG/M <sup>3</sup>	Milligrams per cubic meter	SCBA	Self-Contained Breathing Apparatus
MSHA	Mine Safety and Health Administration	(TP)	Total Particulate
N/A	Not Available	TDG	Transportation of Dangerous Goods
NFPA	National Fire Protection Association	TLV	Threshold Limit Value
NIOSH	National Institute for Occupational Safety and Health	TWA	Time Weighted Average (8 hour)

This SDS (Sections 1-16) was revised on November 09, 2016.

S&S Terminal, Inc. believes the information contained herein is accurate; however, S&S Terminal, Inc. makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein which is not intended to be and should not be construed as legal advice or as insuring compliance with any federal, state, or local laws or regulations. Any party using this product should review all such laws, rules, or regulations prior to use, including but not limited to US and Canada Federal, Provincial, and State regulations.

**NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHERWISE.**